



Section No	A	T	R1	R2	Periphery mm	Mass kg/m
9609	12.70	1.60			51.00	0.189
30211	16.00	1.20	1.60		61.00	0.187
5728	19.00	1.60	2.40	0.80	76.00	0.301
RB-016	19.7	1.00			78.80	0.204
8950	20.00	1.50			80.00	0.300
8777	20.00	3.00	3.00		74.80	0.530
9675	25.00	1.40	2.40	1.00	96.00	0.344
* 6614	25.00	1.60			100.00	0.404
N285	25.00	1.80	3.00		94.85	0.432
9784	25.00	3.00			100.00	0.713
* 6947	30.00	3.00			120.00	0.875
K362	32.00	2.00			128.00	0.65
K026	38.00	1.60	2.00	0.40	148.00	0.623
K911	40.00	1.60			160.00	0.666
G097	40.00	2.00			160.00	0.824
30196	40.00	2.00	2.40		160.00	0.810
X592	40.00	3.00			160.00	1.203
N737	40.00	3.00	3.00	1.00	160.00	1.185
1468	44.45	2.03			178.00	0.930
* J309	50.00	1.60			200.00	0.840
* 5917	50.00	3.00			200.00	1.523
32565	50.00	3.00	3.00		195.00	1.51
32734	50.00	5.00	4.00	2.00	193.00	2.411
X548	50.80	2.03	3.00		203.00	1.023
Z912	60.00	1.40	1.00	0.30	240.00	0.887
K308	65.00	2.50			260.00	1.694
F1942	75.00	1.6			298.00	1.275
K323	75.00	3.00			300.00	2.341
Z320	100.00	3.00			400.00	3.154
F9577	100.00	5.00			399.00	5.13
~ 4059-475	101.60	4.75	4.75		399.00	4.987
~ 40315	150.00	3.00			600.00	4.78

* stock in mill & anodised satin.

~ subject to stock availability at time of order.