



Section No	A	T	R1	R2	Periphery mm	Mass kg/m
9609	12.7	1.6			51	0.189
30211	16	1.2	1.6		61	0.187
5728	19	1.6	2.4	0.8	76	0.301
RB-016	19.7	1.00			78.80	0.204
8950	20	1.5			80	0.3
8777	20	3	3		74.8	0.530
9675	25	1.4	2.4	1	96	0.344
* 6614	25	1.6			100	0.404
N285	25	1.8	3		94.85	0.432
9784	25	3			100	0.713
* 6947	30	3			120	0.875
K362	32	2			128	0.65
K026	38	1.6	2	0.4	148	0.623
K911	40	1.6			160	0.666
G097	40	2			160	0.824
30196	40	2	2.4		160	0.81
X592	40	3			160	1.203
N737	40	3	3	1	160	1.185
1468	44.45	2.03			178	0.93
* J309	50	1.6			200	0.84
* 5917	50	3			200	1.523
32565	50	3	3		195	1.51
32734	50	5	4	2	193	2.411
X548	50.8	2.03	3		203	1.023
Z912	60	1.4	1	0.3	240	0.887
K308	65	2.5			260	1.694
F1942	75	1.6			298	1.275
K323	75	3			300	2.341
Z320	100	3			400	3.154
F9577	100	5			399	5.13
~4059-475	101.6	4.75	4.75		399	4.987
~ 40315	150	3			600	4.78

* stock in mill & anodised satin.

~ subject to stock availability at time of order.