



Section No	A	B	T1	T2	R	Periphery mm	Mass kg/m
J168	10	10	1.6	1.6		57	0.116
* 5978	12	12	1.6	1.6		68.8	0.142
* 0371	12.7	12.7	2.54	2.54		71	0.226
+ X075	14.5	17.95	1.2	1.2	page31	97	0.162
YLJ02571	15	18	1.6	1.6	Note 3	99	0.209
* 5979	16	16	1.6	1.6		92.8	0.194
31017	17	17	1.5	1.5		63	0.17
*YLJ02561	17.6	18.4	1.8	1.8	Note 2	103	0.257
* G862	17.9	18	1.9	1.9	Note 1	102.6	0.257
YLJ02511	18	25	2	2	Note 2	132	0.349
* 5980	20	20	3	3		114	0.437
3470	22.23	12.7	1.57	1.57		92	0.19
* 9335	25	25	1.6	1.6		146.8	0.31
* 4575	25	25	3	3		144	0.559
* 6476	25	40	3	3		204	0.801
* 4087	25	50	3	3		248	1.036
1770	28.58	6.35	1.57	1.57		179	0.161
J088	32	25	3	3		158	0.618
G210	36	36	2.5	2.5		211	0.698
F9531	38	38	3	3		220	0.876
* F9354	40	12	3	3		122	0.472
9677	40	20	1.6	1.6		157	0.332
5982	40	20	3	3		154	0.599
* 6452	40	25	3	3		174	0.68
+31365CHC	40	30/12	1.6	1.6	oddleg	162	0.34
2114	44.5	25	3	3		183	0.717
5983	50	25	3	3		194	0.761
5984	50	50	3	3		294	1.166
+ 8570	51	30	1.5	1.5	page13	227	0.501
+ RB069	53.2	25	1.2	1.2	page11	205	0.328
+ 6330	54	20	1.5	1.5	page12	185	0.369
+ 31348	54	30/45	1.5	1.5	oddleg	255	0.55
+ RB043	55.6	30	1.5	2.3	page12	227	0.504
6330	54	20	1.5	1.5		185	0.369
G743	60	12	3	3		162	0.634
6945	60	32	4	4	4	238	1.257
30487	75	25	3	3		244	0.967
+ K747	78	38	1.5	1.5	page13	305	0.61
+ 31347	79	45/30	1.5	1.5	oddleg	304	0.614
#J458 WEL	80	40	3	3		314	1.252
+ RB301	89	25	1.5	1.5	page11	281	0.569
+ Z381	92	25	2.5	1.5	page15	279	0.769
8716	100	25	3	3		294	1.166
J089	100	50	3	3		394	1.577
6982	100	50	6	6		387	3.046
+ K748	103	38	1.5	1.5	page13	355	0.712
+ RB206	103.2	25	1.6	1.6	page11	301	0.654
+ 31346	104	45/30	1.5	1.5	oddleg	355	0.714
+ Z383	117	25	2.5	1.5	page15	328	0.953
F9783	150	75	3.5	3.5		592	2.768
4760	150	75	5	5		590	3.915
90229A	152.4	88.9	9.5	12.7	11.1	635	9.532
+ E210	160.2	38.5	2	2.3	page13	463	1.245
+ Z382	168	25	2.5	1.5	page15	428	1.326

Note 1: stocked in 2.9m lengths and carried in bright anodised finish.

Note 2: stocked in 2.1m/2.5m/3.0m lengths and carried in bright anodised finish only.

Note 3: stocked in 2.5m lengths and carried in bright anodised finish only.

* stock in mill, anodised & powdercoated finishes.

Stock in our Wellington branch, only (1-2 working day delivery).

+ Stock in Cool Room Sections may have V - grooves. Refer to drawings in coolroom tab.