



Section No	A	T	R	Periphery mm	Mass kg/m
* 6421	12	1.6		48	0.1
5968	12	3		48	0.17
* G466	16	1.6		64	0.132
* 5512	20	1.6		80	0.167
* 5972	20	3		80	0.3
* 5510	25	1.6		100	0.21
* 5973	25	3		100	0.381
* F9125	30	3		120	0.463
F9127	30	6		120	0.875
* K014	32	1.5		128	0.254
+ RB041	38	1.5	page 11	149	0.306
+ RB042	38	1.5	page 11	152	0.311
* 5975	40	1.6		160	0.339
5976	40	3		160	0.624
9530	40	6		160	1.199
+ F4586	50	1.5	page 11	197	0.399
+ F4593	50	1.5	page 11	200	0.404
* 6484	50	1.6		200	0.425
* 5977	50	3		200	0.786
F9632	50	4.5		199	1.16
8518	50	6		200	1.523
9743	60	3		237	0.948
9780	60	6		240	1.847
30543	75	6		299	2.341
5009	76.2	3		305	1.21
5424	76.2	9		305	3.485
F9147	100	6		400	3.154

* stock in mill, anodised & powdercoated finishes.
subject to stock availability at time of order.

+ Stock in Cool Room Sections

+ RB 041 is a 92.5° internal corner angle with 2.0mm thick leg tips
RB 042 is a 87° external corner angle with 2.0mm thick leg tips
F4586 is a 92° internal corner angle with 2.0mm thick leg tips
F4593 is a 87° external corner angle with 2.0mm thick leg tips