



\* Stock in mill, anodised satin.  
Subject to stock availability at time of order.

Section No.	A	B	Corner Radius	Periphery mm	Mass kg/m
DY007	10	3		26	0.081
J791	12	3		30	0.097
9741	12	6		36	0.194
* 5991	16	3		38	0.130
C001	19.05	2.64	1.32	49	0.650
0632	19.05	3.96	1.98	46	0.195
* 5992	20	3		46	0.162
4954	20	6		52	0.325
9336	25	1.6		53	0.108
* 5993	25	3		56	0.205
5996	25	6		62	0.405
32561	25	10		70	0.678
5999	25	12		74	0.810
0340	25.4	4.75		60	0.326
34559	30	3		66	0.244
4999	31.75	12		88	1.029
9337	32	3		70	0.259
# 4996 WEL	38	6		88	0.616
4987	38.1	3		82	0.310
* 6077	40	3		86	0.324
6706	40	6		92	0.684
7426	40	10		100	1.080
J425	40	16		112	1.734
K024	47.65	1.42		98	0.184
* 5994	50	3		106	0.405
5997	50	6		112	0.810
F9447	50	8		116	1.084
7425	50	10		120	1.350
B504	50.8	4.5		110	0.619
J403	60	3		126	0.488
8776	60	6		132	0.972
9777	60	12		144	1.944
5000	63.5	12		151	2.057
* F9061	75	3		158	0.620
F9064	75	10		170	2.048
5662	76.2	6		164	1.234
7040	80	6		172	1.296
J712	100	1.6		203	0.433
* 5995	100	3		206	0.810
Z120	100	5		210	1.360
5998	100	6		212	1.626
8333	100	10		220	2.700
E301	125	6		262	2.033
Z448	150	1.8		212	1.626
K145	150	3		306	1.220
F9391	150	5		310	2.033
9608	160	10		340	4.320
E320	200	10		420	5.420