



Section No.	A	B	T	R1	R2	Periphery mm	Mass kg/m
F9348	20	10	2			60	0.282
K496	37.4	14.4	1.2	3	2	98	0.308
9406	38	25	1.5	3	1.5	121	0.470
X510	38	25	2	3	1.5	121	0.622
30486	40	20	1.6			120	0.493
30485	40	20	3			120	0.878
K582	40	25	2			130	0.661
E905	50	25	1.6			150	0.623
RB-801	50	25	1.6	3		145	0.611
9433	50	25	3			150	1.118
X544	50	25	3	3		145	1.101
RB-142	50	38	2	3		171	0.900
30497	50	40	2			180	0.932
G705	50	40	3			180	1.366
J090	60	40	3			200	1.528
Z357	65	16	1.2	1.5	1	159	0.508
F9503	65	30	2.5			190	1.220
7652	70	40	3			220	1.691
RB-229	75	25	2.2	1.5		197	1.148
30837	75	40	2			229	1.203
K910	80	40	3			240	1.854
6490	80	50	3			260	2.008
30240	80	50	3	5		255	1.995
6669	100	25	2.5			250	1.620
7955	100	45	3			290	2.252
J845	100	50	2			300	1.583
9985	100	50	3			300	2.341
30752	100	50	3	4	1	293	2.307
K102	100	50	6	8		300	4.471
G589	125	40	3			330	2.585
J863	150	50	3			400	3.154
30388	150	75	5	5		414	5.783
Z335	200	50	3			500	3.960
~ 1657	250	50	2			600	3.196
I01039	250	50	3			600	4.780
4480	300	50	3			700	6.507

~ Subject to stock availability at time of order.